

## Technical data sheet



### Shelf life and storage

Unlimited shelf life when stored in a dry and dark place at normal humidity and room temperature

### Order number, article and packaging units

Order-no	Article	PU
07001	250 g tin	24
07002	500 g tin	18

### Sealant and sleeve putty

#### Advantages & Features

- Viscoplastic
- easily kneadable
- strong adhesive power without hardening
- reliable – safe
- Temperature range: -10°C to +100°C
- Color: red

#### Application areas

Putty with strong adhesion power for washstands and water closet bowls as well as sewerage units or sleeves on buried lines.

#### Tests and Approvals

./.

#### Use

With clean hands, model the "plasticine" into the desired shape. The objects to be sealed, such as sleeves, ducts and pipelines, including pipe penetrations in the ground, should be free of dirt, grease and solid residues. Good sealing results are achieved against non-pressing water by massaging in and the high adhesive strength.

**Do not use on marble or other natural stone!**

#### Notice

All information and recommendations contained in this technical data sheet do not represent guaranteed properties. They are based on our research results and experience. However, they are non-binding as we are not responsible for compliance with the processing conditions may be, since we do not know the special application conditions at the user.

A guarantee can only be given for the consistently high quality of our products. We recommend that you conduct sufficient self-tests to determine whether the specified product has the properties you want. A claim from this is excluded. The processor bears sole responsibility for incorrect or inappropriate use.

#### Safety and health

See safety data sheet