



Preshaped sealing tape

For clean and visually appealing seals in the bathroom and the kitchen.

Advantages & Features

Does not yellow

Easy to attach

Colour: white

Resilient

Resistant to water and detergents

Processing temperature: at least 20° C

Application areas

The highly elastic bath sealing tape permits great reliability for a watertight connection of otherwise difficult transition situations.

It is best suited as a seal for bathtub rims, wash basins, showers, kitchen sinks, bathroom furniture, washstands and base cabinets, worktops, urinals, ...

Tests and Approvals

./.

Use

10mm & 15mm joints (Order number 23040 and 23041)

The sealing tape (10mm/15mm) allows an easy and quick installation with a clean and aesthetic result of all the joints in the bathroom and kitchen (bathtub, washbasin...). It is resistant to water, detergents, mold and does not yellow. Do not use to seal an existing seal cover. If there are any old seals, first remove them completely with a cutter knife.

Clean, degrease and dry the desired application area. In order to get a finishing line that is as straight as possible it is advisable to mark the desired upper end edge in advance. Then use scissors to cut the tape at a 45° angle. Cut the angle (see photo). Then attach the trimmed ribbon, starting in a corner. While pressing, apply even pressure to the tape and remove the protective film at the same time. The seal must not be stretched/extended. Then attach the other side in the same way.

40 mm (Order number 23042)

The surface must be absolutely clean, dry, free of grease, dust and free of putty residue. Fold the seal along its entire length so that the plastic sides are on top of each other. Press down kinks. Seals with a width of 40 mm are provided with a two-part protective film. This allows the seal (either top or bottom) to be glued first to one surface (sanitary fixture or wall) and then to the other. By pressing on the still protected half of the seal, the folded edge can be attached at a perfect angle. Keep the profile tape folded and place the folded edge in the angle.

Press firmly with your fingers, perpendicular to the tape, without smoothing the seal (do not stretch the seal). Gradually remove the protective film.

Bath Sealing Tape



Technical data sheet

Processing in corners: Mark the position of the fold for the corner on the profile strip. Cut the lower half of the sealing tape at a 90° angle. Glue the top half around the corner. The lower half comes to lie on top of each other in the corner. Cut the double layer diagonally. Remove the two triangular sections and press the cut ribbon on. The tape sticks immediately.

Shelf life and storage:

3 years shelf life in the originally sealed container

Order number, article and packaging units

Order-no.	Article mm x mm	PU
23040	10 mm x 3,35 mm tape	20
23041	15 mm x 3,35 mm tape	12
23042	40 mm x 3,35 mm tape	12

Notice

All information and recommendations contained in this technical data sheet do not represent guaranteed properties. They are based on our research results and experience. However, they are non-binding as we are not responsible for compliance with the processing conditions may be, since we do not know the special application conditions at the user. A guarantee can only be given for the consistently high quality of our products. We recommend that you conduct sufficient self-tests to determine whether the specified product has the properties you want. A claim from this is excluded. The processor bears sole responsibility for incorrect or inappropriate use.

Safety and health: See safety data sheet