

Technical data sheet



Sealing putty on potassium water glass basis.

Advantages & Properties

- Easy to work with
- Asbestos-free
- Non-shrinking
- Seals well
- Adheres well to metal and other materials
- Non-crumbling
- Fireproof against open fire and temperatures up to over +1000°C
- Water glass base
- Working temperature: +5°C - +40°C
- Curing time: 48h
- Flue gas tight after: 48h

Areas of application

Excellent sealing against flue gases when used on boilers, ovens and cookers. **Not suitable for use on leaks ! Not suitable for exterior use !**

Tests and approvals

./.

Application

The substrates must be load-bearing, dust-free, dry and free from separating agents. Avoid rust, if necessary sand off first. Apply Refractory Boiler Putty generously, overlapping, to the leaking areas with suitable aids and smooth in the bond. If possible, do not expose to open flame during heating. For better application, the boiler putty can be pre-treated with 10% water.

Fermit GmbH

Zur Heide 4 – D-53560 Vettelschoß
Tel.: +49(0)2645 - 2207 / Fax: +49(0)2645 – 3113
Mail: info@fermit.de – Web: www.fermit.de

Shelf life and storage

Cartridge 12 months, can 2 years shelf life in original sealed container.

Storage temperature between +5°C to +30°C

Order no., Article, PU

Order no	Article	PU
11001	250 g tin	24
11002	500 g tin	24
11003	1 kg tin	18
11005	6 kg bucket	Ind.
11006	20 kg bucket	Ind.
11007	310 ml cartridge	12

Note

All information and recommendations contained in this technical data sheet do not represent guaranteed properties. They are based on our **Sealing putty on potassium water glass basis.** research results and experience. However, they are not binding, as we cannot be responsible for compliance with the processing conditions, as we are not familiar with the specific application conditions of the user.

A guarantee can only be given for the consistently high quality of our products. We recommend that you carry out your own tests to determine whether the product specified has the properties you require. A claim arising from this is excluded. The user bears sole responsibility for incorrect or improper use.

Safety and Health

See safety data sheet

Revised	01.06.2021	Seite 1 / 1
---------	------------	-------------