

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.08.2023

Version number 3 (replaces version 2)

Revision: 22.08.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
 - **Trade name: PTFE-Spray Bonnaflon**
 - **UFI:** AW40-103Y-E00W-JFH6
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
 - **Application of the substance / the mixture** Lubricant
- **1.3 Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
Fermit GmbH
Zur Heide 4,
D- 53560 Vettelschoß
www.fermit.de
 - **Informing department:**
Tel.: +49 (0) 2645-2207
Fax: +49 (0) 2645-3113
Email: info@fermit.de
- **1.4 Emergency telephone number:** Tel.: +49 (0) 2645-2207

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1	H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
-----------	--



GHS07

Eye Irrit. 2	H319 Causes serious eye irritation.
STOT SE 3	H336 May cause drowsiness or dizziness.

Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.
-------------------	---

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
acetone
Naphtha (petroleum), hydrotreated light
isopropyl alcohol

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.08.2023

Version number 3 (replaces version 2)

Revision: 22.08.2023

Trade name: PTFE-Spray Bonnaflon

(Contd. from page 1)

- **Hazard statements**

- H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

- P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P280 Wear eye protection / face protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

- **Determination of endocrine-disrupting properties**

The product does not contain substances with endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Mixture of the substances listed below including additives not requiring identification.

- **Dangerous components:**

CAS: 68476-40-4 EINECS: 270-681-9 Reg.nr.: 01-2119486557-22-X	Hydrocarbons, C3-4 ☠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	50 - 100%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-X	acetone ☠ Flam. Liq. 2, H225; ☠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10 - 25%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-X	isopropyl alcohol ☠ Flam. Liq. 2, H225; ☠ Eye Irrit. 2, H319; STOT SE 3, H336	≥ 2.5 - < 10%
CAS: 64742-49-0 EINECS: 265-151-9 Reg.nr.: 01-2119475133-43-X	Naphtha (petroleum), hydrotreated light ☠ Flam. Liq. 2, H225; ☠ Asp. Tox. 1, H304; ☠ Aquatic Chronic 2, H411; ☠ Skin Irrit. 2, H315; STOT SE 3, H336	≥ 2.5 - < 10%

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**

- **General information** Instantly remove any clothing contaminated by the product.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.08.2023

Version number 3 (replaces version 2)

Revision: 22.08.2023

Trade name: PTFE-Spray Bonnaflon

(Contd. from page 2)

- **After inhalation**
Provide fresh air. Keep victims quiet and warm.
In case of persistent symptoms consult doctor.
- **After skin contact**
Wash with water and soap.
If skin irritation continues, consult a doctor.
- **After eye contact**
Rinse opened eye for several minutes under running water.
In case of permanent aches and pains please go and see the doctor.
- **After swallowing**
Rinse out mouth and then drink plenty of water.
Therapy of pertinent symptoms. If symptoms persist seek medical attendance.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents**
CO₂, extinguishing powder or water jet. Fight larger fire with alcohol-resistant foam.
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture**
Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Do not inhale explosion gases or combustion gases.
Use a breathing apparatus that is independent of circulating air when being in closed rooms.
- **Additional information**
Use water spray to keep fire-exposed containers cool.
Remove goods in stock from incendiary zone, if possible.
Collect contaminated fire fighting water separately. It must not enter drains. Provide sufficient fire fighting water retention.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Keep away from ignition sources
Do not inhale vapours.
Observe information for safe handling (item 7) and personal protective equipment (item 8).
- **6.2 Environmental precautions:**
Damp down gases/fumes/haze with water spray jet.
Damaged containers immediately isolate and seal.
Inform respective authorities in case product reaches water or sewage system.
Do not allow to enter drainage system, surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
Clean preferably with cleaning agent; preferably don't use solvents.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.08.2023

Version number 3 (replaces version 2)

Revision: 22.08.2023

Trade name: PTFE-Spray Bonnaflon

See Section 13 for information on disposal.

(Contd. from page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Use only in well ventilated areas.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Avoid contact with eyes and skin.

Keep away from heat and direct sunlight.

Keep empty containers away from heat and ignition sources.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Beware: Container is pressurized. Keep away from direct sun exposure and temperatures over 50°C. Do not open by force or throw into fire even after use.

Do not spray on flames or red-hot objects.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

· **Requirements to be met by storerooms and containers:**

Protect from frost and direct sun exposure.

Observe official regulations on storing packagings with pressurised containers.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Components with limit values that require monitoring at the workplace:**

WEL: workplace exposure limit

OEL: Occupational Exposure Limit

IOELV: Indicative Occupational Exposure Limit Values, workplace threshold value of the European Union

67-64-1 acetone

IOELV (European Union)	Long-term value: 1210 mg/m ³ , 500 ppm
WEL (Great Britain)	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm

67-63-0 isopropyl alcohol

WEL (Great Britain)	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
---------------------	--

· **DNELs**

68476-40-4 Hydrocarbons, C3-4

Dermal	DNEL (worker, long-term, systemic)	23.4 mg/kg bw/day (human)
Inhalative	DNEL (worker, long-term, systemic)	2.21 mg/m ³ (human)
	DNEL (consumer, long-term, systemic)	0.066 mg/m ³ (human)

67-64-1 acetone

Oral	DNEL (consumer, long-term, systemic)	62 mg/kg bw/day (human)
Dermal	DNEL (worker, long-term, systemic)	186 mg/kg bw/day (human)
	DNEL (consumer, long-term, systemic)	62 mg/kg bw/day (human)
Inhalative	DNEL (worker, long-term, systemic)	1,210 mg/m ³ (human)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.08.2023

Version number 3 (replaces version 2)

Revision: 22.08.2023

Trade name: PTFE-Spray Bonnaflon

(Contd. from page 4)

	DNEL (consumer, long-term, systemic)	200 mg/m ³ (human)
	DNEL (worker, short-term, local)	2,420 mg/m ³ (human)
67-63-0 isopropyl alcohol		
Oral	DNEL (consumer, short-term, systemic)	51 mg/kg bw/day (human)
	DNEL (consumer, long-term, systemic)	26 mg/kg bw/day (human)
Dermal	DNEL (worker, long-term, systemic)	888 mg/kg bw/day (human)
	DNEL (consumer, long-term, systemic)	319 mg/kg bw/day (human)
Inhalative	DNEL (worker, short-term, systemic)	1,000 mg/m ³ (human)
	DNEL (worker, long-term, systemic)	500 mg/m ³ (human)
	DNEL (consumer, short-term, systemic)	178 mg/m ³ (human)
	DNEL (consumer, long-term, systemic)	89 mg/m ³ (human)
64742-49-0 Naphtha (petroleum), hydrotreated light		
Inhalative	DNEL (worker, long-term, systemic)	1,286.4 mg/m ³ (human)
	DNEL (consumer, long-term, systemic)	1,152 mg/m ³ (human)
	DNEL (worker, short-term, local)	1,066.67 mg/m ³ (human)
	DNEL (worker, long-term, local)	837.5 mg/m ³ (human)
	DNEL (consumer, short-term, local)	640 mg/m ³ (human)
	DNEL (consumer, long-term, local)	178.57 mg/m ³ (human)

- **PNECs**

67-64-1 acetone

PNEC aqua (freshwater)	10.6 mg/L (.)
PNEC aqua (marine water)	1.06 mg/L (.)
PNEC STP - Sewage Treatment Plant	100 mg/L (.)
PNEC soil	29.5 mg/kg soil dw (.)
PNEC sediment (freshwater)	30.4 mg/kg sedim. dw (.)
PNEC sediment (marine water)	3.04 mg/kg sedim. dw (.)
PNEC aqua (intermittent releases)	21 mg/L (.)

- **Additional information:** The lists that were valid during the compilation were used as basis.

- **8.2 Exposure controls**

- **Individual protection measures, such as personal protective equipment**

- **General protective and hygienic measures**

Do not eat, drink or smoke while working.
Wash hands during breaks and at the end of the work.
Do not inhale gases / fumes / aerosols.

- **Breathing equipment:**

Not necessary if room is well-ventilated.
Use breathing protection in case of insufficient ventilation.
Filter AX.

- **Hand protection**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Butyl rubber, BR

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.08.2023

Version number 3 (replaces version 2)

Revision: 22.08.2023

Trade name: PTFE-Spray Bonnaflon

(Contd. from page 5)

- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
In case of a layer thickness of 0.4 mm the penetration time is longer than 480 minutes.
- **For the permanent contact gloves made of the following materials are suitable:**
Butyl rubber, BR
- **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**
Nitrile rubber, NBR
- **Eye/face protection**



Tightly sealed safety glasses.

- **Body protection:** Not required.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

- | | |
|---|-----------------|
| · Physical state | Aerosol |
| · Colour: | Colourless |
| · Odour: | Aromatic |
| · Odour threshold: | Not determined. |
| · Melting point/freezing point: | Not determined |
| · Boiling point or initial boiling point and boiling range | -44 °C |
| · Flammability | Not applicable. |
| · Lower and upper explosion limit | |
| · Lower: | 1.1 Vol % |
| · Upper: | 15.0 Vol % |
| · Flash point: | -97 °C |
| · Auto-ignition temperature: | 328 °C |
| · Decomposition temperature: | Not determined. |

· SADT

- | | |
|--|------------------------------------|
| · pH | Not determined. |
| · Viscosity: | |
| · Kinematic viscosity | Not determined. |
| · dynamic: | Not applicable.
Not determined. |
| · Solubility | |
| · Water: | Insoluble |
| · Partition coefficient n-octanol/water (log value) | Not determined. |
| · Vapour pressure at 20 °C: | 240 hPa |
| · Density and/or relative density | |
| · Density | Not determined |

· 9.2 Other information

- | | |
|--|------------------------------|
| · Appearance: | |
| · Form: | Aerosol |
| · Important information on protection of health and environment, and on safety. | |
| · Self-inflammability: | Product is not selfigniting. |
| · Explosive properties: | Not determined. |
| · VOC EU | 320.0 g/l |

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.08.2023

Version number 3 (replaces version 2)

Revision: 22.08.2023

Trade name: PTFE-Spray Bonnaflon

(Contd. from page 6)

· VOC EU	32.00 %
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Strong oxidizing agents
- **10.6 Hazardous decomposition products:**
None in case of intended use and storage in compliance with instructions.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

68476-40-4 Hydrocarbons, C3-4

Oral	LD50	> 2,000 mg/kg (rat) (OECD 401)
Inhalative	LC50	5.8 mg/l/4h (rat) (OECD 403)

67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	> 7,426 mg/kg (guinea pig) (21 CFR 191.10) > 7,426 mg/kg (rabbit) (21 CFR 191.10)
Inhalative	LC50	132 mg/l/3h (rat)

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.08.2023

Version number 3 (replaces version 2)

Revision: 22.08.2023

Trade name: PTFE-Spray Bonnaflon

(Contd. from page 7)

67-63-0 isopropyl alcohol

Oral	LD50	5,840 mg/kg (rat) (OECD 401)
Dermal	LD50	13,400 mg/kg (rabbit)
Inhalative	LC50	30 mg/l/4h (rat) Vapour

64742-49-0 Naphtha (petroleum), hydrotreated light

Oral	LD50	> 6,000 mg/kg (rat)
Dermal	LD50	> 3,000 mg/kg (rabbit)
Inhalative	LC50	> 32 mg/l/4h (rat)

- **Skin corrosion/irritation**

More frequent and continuous contact with the skin may result in irritation of the skin.

- **Serious eye damage/irritation** Splashes can cause temporary eye irritation.

- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

- **Carcinogenicity** Based on available data, the classification criteria are not met.

- **Reproductive toxicity** Based on available data, the classification criteria are not met.

- **STOT-single exposure**

May cause drowsiness or dizziness.

- **STOT-repeated exposure** Based on available data, the classification criteria are not met.

- **Aspiration hazard** Based on available data, the classification criteria are not met.

- **Additional toxicological information:**

- **Repeated dose toxicity**

67-64-1 acetone

Oral	NOAEL (90d)	3,100 mg/kg bw/day (rat) (OECD 408)
------	-------------	-------------------------------------

64742-49-0 Naphtha (petroleum), hydrotreated light

Oral	NOAEL (90d)	100 mg/kg bw/day (rat) (OECD 408)
------	-------------	-----------------------------------

- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

68476-40-4 Hydrocarbons, C3-4

EC50	10 mg/l/48h (Daphnia magna) (OECD 202)
LC50	5.3 mg/l/96h (Oncorhynchus mykiss) (OECD 203)
EC50	32 mg/l/72h (Raphidocelis subcapitata) (OECD 201)

67-64-1 acetone

EC50	> 10,000 mg/l/24h (Daphnia magna)
LC50 (dynamic)	8,120 mg/l/96h (Pimephales promelas) (OECD 203)

67-63-0 isopropyl alcohol

EC50 (static)	> 10,000 mg/l/24h (Daphnia magna) (OECD202)
LC50 (dynamic)	9,640 mg/l/96h (Pimephales promelas) (OECD203)

64742-49-0 Naphtha (petroleum), hydrotreated light

EC50 (static)	4.5 mg/l/48h (Daphnia magna) (OECD 202)
EC50 (static)	3.7 mg/l/96h (Raphidocelis subcapitata) (OECD 201)
LC50	8.2 mg/l/96h (Pimephales promelas) (EPA 66013-75-009)

- **12.2 Persistence and degradability** No further relevant information available.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.08.2023

Version number 3 (replaces version 2)

Revision: 22.08.2023

Trade name: PTFE-Spray Bonnaflon

(Contd. from page 8)

- **Other information:** There are no data available about the preparation.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
 - **Additional ecological information:**
 - **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
The waste code numbers mentioned are recommendations based on the probable use of the product.

- **European waste catalogue**

14 00 00	WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08)
14 06 00	waste organic solvents, refrigerants and foam/aerosol propellants
14 06 03*	other solvents and solvent mixtures
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP14	Ecotoxic

- **Uncleaned packagings:**
 - **Recommendation:**
Non contaminated packagings can be used for recycling.
Packagings that cannot be cleaned are to be disposed of in the same manner as the product.

SECTION 14: Transport information

- | | |
|---|--|
| <ul style="list-style-type: none"> · 14.1 UN number or ID number · ADR/RID, IMDG, IATA | UN1950 |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR/RID · IMDG · IATA | 1950 AEROSOLS
AEROSOLS
AEROSOLS, flammable |

- **14.3 Transport hazard class(es)**

- **ADR/RID**



- **Class** 2 5F Gases.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31


Printing date 22.08.2023

Version number 3 (replaces version 2)

Revision: 22.08.2023

Trade name: PTFE-Spray Bonnaflon

(Contd. from page 9)

· Label	2.1
· IMDG, IATA	
	
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group	
· ADR/RID, IMDG, IATA	Void
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Gases.
· Kemler Number:	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR/RID	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

EU

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.08.2023

Version number 3 (replaces version 2)

Revision: 22.08.2023

Trade name: PTFE-Spray Bonnaflon

(Contd. from page 10)

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P3a FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

67-64-1	acetone
---------	---------

· **Regulation (EC) No 273/2004 on drug precursors**

67-64-1	acetone	3
---------	---------	---

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

67-64-1	acetone	3
---------	---------	---

· **National regulations**

· **Water hazard class:**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is contained.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· **Department issuing data specification sheet:**

- ▶ **DEKRA** This Safety Data Sheet has been drawn up in cooperation with:
 DEKRA Assurance Services GmbH, Hanomagstr. 12, D-30449 Hanover, Germany,
 phone: (+49) 511 42079 - 0, reach@dekra.com.

© DEKRA Assurance Services GmbH. Changing this documents is subject to explicit acceptance by DEKRA Assurance Services GmbH.

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.08.2023

Version number 3 (replaces version 2)

Revision: 22.08.2023

Trade name: PTFE-Spray Bonnaflon

(Contd. from page 11)

- **Version number of previous version: 2**

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- *** Data compared to the previous version altered.**

EU