

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.07.2018

Version number 2

Revision: 02.07.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Silikonspray AOFIX**
- **UFI-Code:** VT40-H0EK-400E-V3X4
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Lubricant
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Fermit GmbH
Zur Heide 4,
D- 53560 Vettelschoß
www.fermit.de
- **Informing department:**
Tel.: +49 (0) 2645-2207
Fax: +49 (0) 2645-3113
Email: info@fermit.de
- **1.4 Emergency telephone number:** Tel.: +49 (0) 2645-2207

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
Naphtha (petroleum), hydrodesulfurized heavy
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319 Causes serious eye irritation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.07.2018

Version number 2

Revision: 02.07.2018

Trade name: Silikonspray AOFIX

(Contd. from page 1)

Precautionary statements

- P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P280 Wear eye protection / face protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards
Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

- **Description:** Mixture of the substances listed below including additives not requiring identification.

Dangerous components:

CAS: 64742-82-1 EINECS: 265-185-4 Reg.nr.: 01-2119490979-12-X	Naphtha (petroleum), hydrodesulfurized heavy ⚠ Asp. Tox. 1, H304	25 - 50%
CAS: 68476-40-4 EINECS: 270-681-9 Reg.nr.: 01-2119486557-22-X	Hydrocarbons, C3-4 ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	25 - 50%
CAS: 78-83-1 EINECS: 201-148-0 Reg.nr.: 01-2119484609-23-X	butanol ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335-H336	≥ 1 - < 2.5%

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- **General information** Instantly remove any clothing contaminated by the product.
- **After inhalation**
Provide fresh air. Keep victims quiet and warm.
In case of persistent symptoms consult doctor.
- **After skin contact**
Wash with water and soap.
If skin irritation continues, consult a doctor.
- **After eye contact**
Rinse opened eye for several minutes under running water.
In case of permanent aches and pains please go and see the doctor.
- **After swallowing**
Rinse out mouth and then drink plenty of water.
Therapy of pertinent symptoms. If symptoms persist seek medical attendance.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.07.2018

Version number 2

Revision: 02.07.2018

Trade name: Silikonspray AOFIX

(Contd. from page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents**
CO₂, extinguishing powder or water jet. Fight larger fire with alcohol-resistant foam.
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture**
Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Do not inhale explosion gases or combustion gases.
Use a breathing apparatus that is independent of circulating air when being in closed rooms.
- **Additional information**
Cool closed containers near by fire source with water.
Collect contaminated fire fighting water separately. It must not enter drains. Provide sufficient fire fighting water retention.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Keep away from ignition sources
Do not inhale vapours.
Observe information for safe handling (item 7) and personal protective equipment (item 8).
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Damp down gases/fumes/haze with water spray jet.
Damaged containers immediately isolate and seal.
Inform respective authorities in case product reaches water or sewage system.
Do not allow to enter drainage system, surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
Clean preferably with cleaning agent; preferably don't use solvents.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Use only in well ventilated areas.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Avoid contact with eyes and skin.
Keep away from heat and direct sunlight.
Keep empty containers away from heat and ignition sources.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Beware: Container is pressurized. Keep away from direct sun exposure and temperatures over 50°C. Do not open by force or throw into fire even after use.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.07.2018

Version number 2

Revision: 02.07.2018

Trade name: Silikonspray AOFIX

(Contd. from page 3)

Do not spray on flames or red-hot objects.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage**

- **Requirements to be met by storerooms and containers:**

Protect from frost and direct sun exposure.

Observe official regulations on storing packagings with pressurised containers.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Components with limit values that require monitoring at the workplace:**

WEL: workplace exposure limit

78-83-1 butanol	
WEL (Great Britain)	Short-term value: 231 mg/m ³ , 75 ppm Long-term value: 154 mg/m ³ , 50 ppm

- **DNELs**

64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy		
Inhalative	DNEL (worker, short-term, systemic)	1,300 mg/m ³ (human)
	DNEL (consumer, short-term, systemic)	1,200 mg/m ³ (human)
	DNEL (worker, short-term, local)	1,100 mg/m ³ (human)
	DNEL (worker, long-term, local)	840 mg/m ³ (human)
	DNEL (consumer, short-term, local)	640 mg/m ³ (human)
	DNEL (consumer, long-term, local)	180 mg/m ³ (human)

- **Additional information:** The lists that were valid during the compilation were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment**

- **General protective and hygienic measures**

Do not eat, drink or smoke while working.

Wash hands during breaks and at the end of the work.

Do not inhale gases / fumes / aerosols.

- **Breathing equipment:**

Not necessary if room is well-ventilated.

Use breathing protection in case of insufficient ventilation.

Filter AX.

- **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Butyl rubber, BR

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.07.2018

Version number 2

Revision: 02.07.2018

Trade name: Silikonspray AOFIX

(Contd. from page 4)

- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
In case of a layer thickness of 0.4 mm the penetration time is longer than 480 minutes.
- **For the permanent contact gloves made of the following materials are suitable:**
Butyl rubber, BR
- **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**
Nitrile rubber, NBR
- **Eye protection:**



Tightly sealed safety glasses.

- **Body protection:** Not required.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Aerosol
Colour:	White
Odour:	Aromatic
Odour threshold:	Not determined.

· **pH-value:** Not determined.

· Change in condition

Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	-44 °C

· **Flash point:** -97 °C

· **Inflammability (solid, gaseous)** Not applicable.

· **Ignition temperature:** 460 °C

· **Decomposition temperature:** Not determined.

· **Self-inflammability:** Product is not selfigniting.

· **Explosive properties:** Not determined.

· Critical values for explosion:

Lower:	1.8 Vol %
Upper:	15.0 Vol %

· **Vapour pressure at 20 °C:** 8300 hPa

· **Density** Not determined

· **Evaporation rate** Not determined.

· Solubility in / Miscibility with

Water: Insoluble

· **Partition coefficient: n-octanol/water:** Not determined.

· Viscosity:

dynamic: Not applicable.

Not determined.

kinematic: Not determined.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.07.2018

Version number 2

Revision: 02.07.2018

Trade name: Silikonspray AOFIX

(Contd. from page 5)

- **Solvent content:**
- **Organic solvents:**
 - VOC EU 24.0 g/l
 - VOC EU 2.40 %
- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Strong oxidizing agents
- **10.6 Hazardous decomposition products:**
None in case of intended use and storage in compliance with instructions.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy

Oral	LD50	> 5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 2,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50	> 5.61 mg/l/4h (rat) (OECD 403)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
More frequent and continuous contact with the skin may result in irritation of the skin.
- **Serious eye damage/irritation**
Splashes can cause temporary eye irritation.
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy

EC50	4.5 mg/l/48h (Daphnia magna) (OECD 202)
------	---

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.07.2018

Version number 2

Revision: 02.07.2018

Trade name: Silikonspray AOFIX

(Contd. from page 6)

EC50	3.7 mg/l/96h (Pseudokirchneriella subcapitata) (OECD 201)
LC50	8.2 mg/l/96h (Pimephales promelas) (EPA 66013-75-009)
EC50	3.1 mg/l/72h (Pseudokirchneriella subcapitata) (OECD 201)

- **12.2 Persistence and degradability** No further relevant information available.
- **Other information:** There are no data available about the preparation.
- **Behaviour in environmental systems:**
- **Components:**
A product that has flown out can lead to the formation of a film on the water surface which reduces the oxygen exchange and results in the organisms dying-off.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.
Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
The waste code numbers mentioned are recommendations based on the probable use of the product.

- **European waste catalogue**

14 00 00	WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (except 07 and 08)
14 06 00	waste organic solvents, refrigerants and foam/aerosol propellants
14 06 03*	other solvents and solvent mixtures

- **Uncleaned packagings:**
- **Recommendation:**
Non contaminated packagings can be used for recycling.
Packagings that cannot be cleaned are to be disposed of in the same manner as the product.

SECTION 14: Transport information

- | | |
|---|--|
| <ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA | UN1950 |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA | 1950 AEROSOLS
AEROSOLS
AEROSOLS, flammable |

(Contd. on page 8)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.07.2018

Version number 2

Revision: 02.07.2018

Trade name: **Silikonspray AOFIX**

(Contd. from page 7)

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 2 5F Gases.
· **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1
· **Label** 2.1

· **14.4 Packing group**

· **ADR, IMDG, IATA** Void

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

· **Warning:** Gases.
· **Kemler Number:** -
· **EMS Number:** F-D,S-U
· **Stowage Code** SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

· **Segregation Code**

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 1L
· **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity
· **Transport category** 2
· **Tunnel restriction code** D

· **IMDG**

· **Limited quantities (LQ)** 1L
· **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity

· **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

GB

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.07.2018

Version number 2

Revision: 02.07.2018

Trade name: Silikonspray AOFIX

(Contd. from page 8)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 - **Directive 2012/18/EU**
 - **Named dangerous substances - ANNEX I** None of the ingredients is listed.
 - **Seveso category** P3a FLAMMABLE AEROSOLS
 - **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
 - **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
 - **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
 - **National regulations**
 - **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
 - **Substances of very high concern (SVHC) according to REACH, Article 57**
- None of the ingredients is contained.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 H220 Extremely flammable gas.
 H226 Flammable liquid and vapour.
 H280 Contains gas under pressure; may explode if heated.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
- **Department issuing data specification sheet:**
 This Material Safety Data Sheet has been drawn up in cooperation with:
 DEKRA Assurance Services GmbH, Hanomagstr. 12, D-30449 Hanover, Germany,
 phone: (+49) 511 42079 - 0, reach@dekra.com.
 © DEKRA Assurance Services GmbH. Changing this documents is subject to explicit acceptance by DEKRA Assurance Services GmbH.
- **Abbreviations and acronyms:**
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative
 Flam. Gas 1: Flammable gases – Category 1
 Aerosol 1: Aerosols – Category 1
 Press. Gas (Comp.): Gases under pressure – Compressed gas
 Flam. Liq. 3: Flammable liquids – Category 3
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.07.2018

Version number 2

Revision: 02.07.2018

Trade name: Silikonspray AOFIX

Asp. Tox. 1: Aspiration hazard – Category 1

(Contd. from page 9)

· *** Data compared to the previous version altered.**

GB