

Printing date 28.03.2017 Version number 1 Revision: 28.03.2017

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Entfetter Spray
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
  No further relevant information available.
- · Application of the substance / the mixture Detergent spray
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Fermit GmbH Zur Heide 4, D- 53560 Vettelschoß www.fermit.de

Informing department:

Tel.: +49 (0) 2645-2207 Fax: +49 (0) 2645-3113 Email: info@fermit.de

• 1.4 Emergency telephone number: Tel.: +49 (0) 2645-2207

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS09

Printing date 28.03.2017 Version number 1 Revision: 28.03.2017

Trade name: Entfetter Spray

(Contd. from page 1)

· Signal word Danger

#### · Hazard-determining components of labelling:

Solvent naphtha (petroleum), light aliph. acetone

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P280 Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 ℃/122 ℉.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of the substances listed below including additives not requiring identification.

Dangerous components:		
	Solvent naphtha (petroleum), light aliph.  Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	50 - 100%
	acetone  Trit. 2, H319; STOT SE 3, H336	10 - 25%
	isobutane Flam. Gas 1, H220; Press. Gas C, H280	≤10%
	propane Flam. Gas 1, H220; Press. Gas C, H280	≤10%
EINECS: 204-696-9	carbon dioxide  Press. Gas L, H280	2.5-<10%

· Additional information For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation Take affected persons into the open air and position comfortably
- · After skin contact

Wash with water and soap.

In cases of freeze burns, rinse with plenty of water. Do not remove clothing.

(Contd. on page 3)

Printing date 28.03.2017 Version number 1 Revision: 28.03.2017

Trade name: Entfetter Spray

(Contd. from page 2)

· After eye contact

Rinse opened eye for several minutes under running water.

In case of permanent aches and pains please go and see the doctor.

- · After swallowing Swallowing is not considered to be a possible way of exposure.
- 4.2 Most important symptoms and effects, both acute and delayed drowsiness

Dazed

4.3 Indication of any immediate medical attention and special treatment needed
 No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fire with alcohol-resistant foam.

- · For safety reasons unsuitable extinguishing agents Water with a full water jet.
- · 5.2 Special hazards arising from the substance or mixture

Pressure build-up and risk of bursting when heated.

During incomplete combustion carbon monoxide can be formed.

Vapours are heavier than air and may travel long distances along ground, ignite and flash back to source.

- · 5.3 Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

In case of fire wear breathing equipment being independent of ambient air and suit provided full protection against chemicals.

· Additional information

Cool endangered containers with water spray.

Remove goods in stock from incendiary zone, if possible.

### SECTION 6: Accidental release measures

### · 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from sources of ignition - No smoking.

Avoid contact with eyes, skin and clothes.

Do not inhale vapours.

- 6.2 Environmental precautions: Damp down gases/fumes/haze with water spray jet.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

## SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Keep away from heat and direct sunlight.

Keep empty containers away from heat and ignition sources.

Do not spray into the eyes.

### Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Beware: Container is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use.

(Contd. on page 4)

Printing date 28.03.2017 Version number 1 Revision: 28.03.2017

Trade name: Entfetter Spray

(Contd. from page 3)

Do not spray on flames or red-hot objects.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and containers:

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Keep away from food, drink and animal feeding stuffs.

Do not store together with oxidizing or self-igniting substances.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with limit values that require monitoring at the workplace:

WEL: workplace exposure limit

TTEE. Workplace expectate time		
67-64-1 acetone	-1 acetone	
WEL (Great Britain)	Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm	
IOELV (European Union)	uropean Union) Long-term value: 1210 mg/m³, 500 ppm	
124-38-9 carbon dioxide		
WEL (Great Britain)	Short-term value: 27400 mg/m³, 15000 ppm Long-term value: 9150 mg/m³, 5000 ppm	
IOELV (European Union)	Long-term value: 9000 mg/m³, 5000 ppm	

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment
- General protective and hygienic measures

Avoid contact with the eyes and skin.

Do not eat, drink or smoke while working.

Wash hands during breaks and at the end of the work.

Do not inhale gases / fumes / aerosols.

· Breathing equipment:

Not necessary if room is well-ventilated.

Use breathing protection in case of insufficient ventilation.

Filter AX.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

(Contd. on page 5)

Printing date 28.03.2017 Version number 1 Revision: 28.03.2017

Trade name: Entfetter Spray

(Contd. from page 4)

Butyl rubber, BR Fluorocarbon rubber (Viton)

· Eye protection:



Tightly sealed safety glasses.

· Body protection:

Wear antistatic clothing made from natural fibres (cotton) or heat-resistant synthetic fibres.

· Limitation and supervision of exposure into the environment

Avoid the uncontrolled release into the environment.

## SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:
Colour:
Colourless
Odour:
Characteristic
Not determined.

· **pH-value:** Not determined.

· Change in condition

**Melting point/freezing point:** Not determined

Initial boiling point and boiling range: Not applicable, as aerosol

Flash point: ca. -80 °C
 Inflammability (solid, gaseous) Not applicable.

· Ignition temperature: 235 °C

· **Decomposition temperature:** Not determined.

• Explosive properties: Not determined.

· Critical values for explosion:

 Lower:
 1.4 Vol %

 Upper:
 13 Vol %

· Vapour pressure: 5200 hPa

Density
 Evaporation rate
 0.73 g/cm<sup>3</sup>
 Not applicable.

· Solubility in / Miscibility with

Water: Partly soluble

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

dynamic: Not determined. kinematic: Not determined.

• 9.2 Other information No further relevant information available.

## SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

(Contd. on page 6)

Printing date 28.03.2017 Version number 1 Revision: 28.03.2017

Trade name: Entfetter Spray

(Contd. from page 5)

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

Avoid direct sunlight, heat and ignition sources.

10.3 Possibility of hazardous reactions

Danger of containers bursting because of high vapour pressure

- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: Strong oxidizing agents
- · 10.6 Hazardous decomposition products:

None in case of intended use and storage in compliance with instructions.

## SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard

May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · Other information: There are no data available about the preparation.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Proceed according to local, official regulations.

The waste code numbers mentioned are recommendations based on the probable use of the product.

(Contd. on page 7)

Printing date 28.03.2017 Version number 1 Revision: 28.03.2017

Trade name: Entfetter Spray

	(Contd. from page 6					
	· European waste catalogue					
Ī	16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST				
	16 05 00	gases in pressure containers and discarded chemicals				
	16 05 04*	gases in pressure containers (including halons) containing hazardous substances				
	14 00 00	WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08)				
	14 06 00	waste organic solvents, refrigerants and foam/aerosol propellants				
	14 06 03*	other solvents and solvent mixtures				

- · Uncleaned packagings:
- Recommendation:

After use the packaging shall be discharged completely. Dispose of packaging according to regulations on the disposal of packagings.

SECTION 14: Transport information		
· 14.1 UN-Number · ADR, IMDG, IATA	UN1950	
· 14.2 UN proper shipping name · ADR	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS	
· IMDG · IATA	AEROSOLS, MARINE POLLUTANT Aerosols, flammable	
· 14.3 Transport hazard class(es)		
ADR		
· Class · Label	2 5F Gases. 2.1	
· IMDG		
· Class · Label	2.1 2.1	
· IATA		
· Class · Label	2.1 2.1	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards: · Marine pollutant:	Symbol (fish and tree)	

Printing date 28.03.2017 Version number 1 Revision: 28.03.2017

Trade name: Entfetter Spray

	(Contd. from page
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user · Kemler Number: · EMS Number: · Stowage Code	Warning: Gases. 23 F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Anr of Marpol and the IBC Code	nex II  Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category	1L Code: E0 Not permitted as Excepted Quantity 2
Tunnel restriction code IMDG	D
· Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

## SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

  The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms







GHS02 GHS07 GHS09

- · Signal word Danger
- · Hazard-determining components of labelling:

Solvent naphtha (petroleum), light aliph. acetone

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

(Contd. on page 9)

Revision: 28.03.2017 Printing date 28.03.2017 Version number 1

Trade name: Entfetter Spray

(Contd. from page 8) Toxic to aquatic life with long lasting effects.

H411

· Precautionary statements

Keep out of reach of children. P102

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Do not spray on an open flame or other ignition source. P211

P251 Do not pierce or burn, even after use.

P280 Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 ℃/122 ℉.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations
- · Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is contained.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### Department issuing data specification sheet:

This Material Safety Data Sheet has been drawn up in cooperation with:

DEKRA Assurance Services GmbH, Hanomagstr. 12, D-30449 Hanover, Germany,

phone: (+49) 511 42079 - 0, reach@dekra.com.

© DEKRA Assurance Services GmbH. Changing this documents is subject to explicit acceptance by DEKRA Assurance Services GmbH.

#### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure - Compressed gas

(Contd. on page 10)

Page 10/10

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.03.2017 Version number 1 Revision: 28.03.2017

Trade name: Entfetter Spray

Press. Gas L: Gases under pressure – Liquefied gas
Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

(Contd. from page 9)