

Printing date 17.04.2018 Version number 1 Revision: 17.04.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: PVC-Kleber blau
- · UFI-Code: 7300-P0FR-9006-GAVK
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Fermit GmbH Zur Heide 4, D- 53560 Vettelschoß www.fermit.de

Informing department:

Tel.: +49 (0) 2645-2207 Fax: +49 (0) 2645-3113 Email: info@fermit.de

• 1.4 Emergency telephone number: Tel.: +49 (0) 2645-2207

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS02 GHS05 GHS07

Printing date 17.04.2018 Version number 1 Revision: 17.04.2018

Trade name: PVC-Kleber blau

(Contd. from page 1)

· Signal word Danger

· Hazard-determining components of labelling:

cyclohexanone butanone

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves / eye protection.
P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of the substances listed below including additives not requiring identification.

· Dangerous components:		
	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	50 - 100%
EINECS: 203-631-1	cyclohexanone	10 - 25%
EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-X	xylene, mixed isomers, pure Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	≥ 2.5 - < 10%

[·] Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information Instantly remove any clothing contaminated by the product.
- · After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact

Remove contaminated clothing.

Wash intensively with water and soap. Use protective skin ointment.

(Contd. on page 3)

Printing date 17.04.2018 Version number 1 Revision: 17.04.2018

Trade name: PVC-Kleber blau

(Contd. from page 2)

Wash contaminated clothing before re-use.

· After eye contact

Keep eye lids open and rinse them with ample amounts of clean running water for at least 15 minutes.

Seek immediate medical advice.

· After swallowing

Rinse out mouth.

Avoid vomiting. Don't give anything to drink. Immediately consult physician.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

Extinguishing powder, foam or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- · For safety reasons unsuitable extinguishing agents Water with a full water jet.
- · 5.2 Special hazards arising from the substance or mixture

Can be released in case of fire:

Carbon monoxide and carbon dioxide

Formation of flammable mixtures of vapours with air possible.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained breathing apparatus.
- · Additional information Cool endangered containers with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from sources of ignition and care for sufficient ventilation due to the content of organic solvents.

Do not inhale vapours.

6.2 Environmental precautions:

Do not allow to enter drainage system, surface or ground water.

Inform respective authorities in case product reaches water or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Prevent formation of aerosols.

Avoid contact with eyes, skin and clothes.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

Printing date 17.04.2018 Version number 1 Revision: 17.04.2018

Trade name: PVC-Kleber blau

(Contd. from page 3)

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

Vapours are heavier than air and may travel long distances along ground, ignite and flash back to source.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and containers:

Store cool and dry in well sealed containers.

Ensure sufficient ventilation.

· Information about storage in one common storage facility:

Keep away from food, drink and animal feeding stuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with limit values that require monitoring at the workplace:

WEL: workplace exposure limit

IOELV: Indicative Occupational Exposure Limit Values, workplace threshold value of the European Union

78-93-3 butanone	
WEL (Great Britain)	Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV
IOELV (European Union)	Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm
108-94-1 cyclohexanone	
WEL (Great Britain)	Short-term value: 82 mg/m³, 20 ppm Long-term value: 41 mg/m³, 10 ppm Sk, BMGV
IOELV (European Union)	Short-term value: 81.6 mg/m³, 20 ppm Long-term value: 40.8 mg/m³, 10 ppm Skin
1330-20-7 xylene, mixed	isomers, pure
WEL (Great Britain)	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV
IOELV (European Union)	Short-term value: 442 mg/m³, 100 ppm Long-term value: 221 mg/m³, 50 ppm Skin
· DNELs	
78-93-3 butanone	
Oral DNEL (consun	ner, long-term, systemic) 31 mg/kg bw/day (human)
Dayman DNEL (4 4 6 4

78-93-3 butanone Oral DNEL (consumer, long-term, systemic) Dermal DNEL (worker, long-term, systemic) DNEL (consumer, long-term, systemic) Inhalative DNEL (worker, long-term, systemic) DNEL (consumer, long-term, systemic)

· PNECs	
78-93-3 butanone	
PNEC aqua (freshwater)	55.8 mg/L (.)

(Contd. on page 5)

Printing date 17.04.2018 Version number 1 Revision: 17.04.2018

Trade name: PVC-Kleber blau

				(Contd. from page 4)
	PNEC aqua (marine w	vater)	55.8 mg/L (.)	
	PNEC STP		709 mg/L (.)	
	PNEC soil		22.5 mg/kg soil dw (.)	
	PNEC sediment (fresh	nwater)	284.7 mg/kg sedim. dw (.)	
	PNEC sediment (mari	ne water)	284.7 mg/kg sedim. dw (.)	
	PNEC aqua (intermitte	ent releases)	55.8 mg/L (.)	
	PNEC oral		1,000 mg/kg food (.)	
Ī	· Ingredients with biol	logical limit	values:	
	78-93-3 butanone			
	BMGV (Great Britain)	70 μmol/L		
		Medium: urii		
Sampling tin				
		Parameter: I	butan-2-one	
	108-94-1 cyclohexan	one		
	BMGV (Great Britain)	2 mmol/mol	creatinine	
		Medium: urii		
			ne: post shift	
			cyclohexanol	
	1330-20-7 xylene, mixed isomers, pure			
	BMGV (Great Britain)			
		Medium: urii		
			ne: post shift	
		Parameter: ı	methyl hippuric acid	

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment
- General protective and hygienic measures

Wash hands always after use.

Keep away from foodstuffs, beverages and food.

Take off all contaminated clothing immediately.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

Breathing equipment:

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

There is no suitable material for protective gloves for this substance. The recommended protective glove has to be replaced often

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Printing date 17.04.2018 Version number 1 Revision: 17.04.2018

Trade name: PVC-Kleber blau

(Contd. from page 5)

In case of a layer thickness of 0.7 mm the penetration time is longer than 60 minutes.

- As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR
- · Eye protection:



Tightly sealed safety glasses.

· Body protection:

Wear antistatic clothing made from natural fibres (cotton) or heat-resistant synthetic fibres.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Colour: Blue
• Odour: Aromatic

· Change in condition

Melting point/freezing point: Not determined

Initial boiling point and boiling range: > 35 ℃

· Flash point: -4 °C

· **Self-inflammability:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/steam mixtures is possible.

· Vapour pressure: Not determined.

· **Density** Not determined

Relative density < 1

· Solubility in / Miscibility with

Water: Insoluble

· Viscosity:

dynamic:Not determined.kinematic:Not determined.

· Solvent content:

· Organic solvents:

VOC EU 734 g/L

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 7)

Printing date 17.04.2018 Version number 1 Revision: 17.04.2018

Trade name: PVC-Kleber blau

(Contd. from page 6)

· 10.6 Hazardous decomposition products: None at intended use.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification:

78-93-3 butanone

Oral LD50 3,460 mg/kg (rat) (OECD 423)

Dermal LD50 5,000 mg/kg (rabbit)

- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eve damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

78-93-3 butanone

EC50 (static) 308 mg/l/48h (Daphnia magna) (OECD 202)

EC50 (static) 2,029 mg/l/96h (Pseudokirchneriella subcapitata) (OECD 201)

LC50 (static) 2,993 mg/l/96h (Pimephales promelas) (OECD 203)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

- 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

GB

Printing date 17.04.2018 Version number 1 Revision: 17.04.2018

Trade name: PVC-Kleber blau

(Contd. from page 7)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

The waste code numbers mentioned are recommendations based on the probable use of the product.

· European waste catalogue				
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS			
08 04 00	wastes from MFSU of adhesives and sealants (including waterproofing products)			
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances			
HP 3	Flammable			
HP 4	Irritant - skin irritation and eye damage			
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity			
HP 6	Acute Toxicity			

- · Uncleaned packagings:
- · Recommendation:

Dispose of packaging according to regulations on the disposal of packagings.

Packaging can be reused or recycled after cleaning.

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN1133
- · 14.2 UN proper shipping name
- · ADR 1133 ADHESIVES, special provision 640D
- · IMDG, IATA ADHESIVES
- · 14.3 Transport hazard class(es)
- · ADR



- · *Class* 3 (F1) Flammable liquids.
- · Label
- · IMDG, IATA



- · Class 3 Flammable liquids.
- · Label
- · 14.4 Packing group
- · ADR, IMDG, IATA

(Contd. on page 9)

Printing date 17.04.2018 Version number 1 Revision: 17.04.2018

Trade name: PVC-Kleber blau

	(Contd. from page
· 14.5 Environmental hazards: · Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
· Kemler Number:	33
· EMS Number:	F-E,S-D B
· Stowage Category	
· 14.7 Transport in bulk according to An	
of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
Turnen aut antonomi	Maximum net quantity per outer packaging: 500 m
· Transport category	2 D/E
· Tunnel restriction code	D/E
· IMDG	
Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 m
· UN "Model Regulation":	UN 1133 ADHESIVES, SPECIAL PROVISION 640D, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- · National regulations
- · Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is contained.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

(Contd. on page 10)

Revision: 17.04.2018 Printing date 17.04.2018 Version number 1

Trade name: PVC-Kleber blau

(Contd. from page 9)

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eve irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Department issuing data specification sheet:

This Material Safety Data Sheet has been drawn up in cooperation with:

DEKRA Assurance Services GmbH, Hanomagstr. 12, D-30449 Hanover, Germany,

phone: (+49) 511 42079 - 0, reach@dekra.com.

© DEKRA Assurance Services GmbH. Changing this documents is subject to explicit acceptance by DEKRA Assurance Services GmbH.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1