

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.04.2018

Version number 1

Revision: 17.04.2018

Page 1/9

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

- · Trade name: Reparatur-Set für Pool-Folien
- · UFI-Code: VF00-Q07A-H005-4Q6U
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesives
- 1.3 Details of the supplier of the safety data sheet
   Manufacturer/Supplier: Fermit GmbH
   Zur Heide 4,
   D- 53560 Vettelschoß
- *Informing department:* Tel.: +49 (0) 2645-2207 Fax: +49 (0) 2645-3113 Email: info@fermit.de

www.fermit.de

• 1.4 Emergency telephone number: Tel.: +49 (0) 2645-2207

# **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.

GHS07

Eye Irrit. 2H319Causes serious eye irritation.STOT SE 3H336May cause drowsiness or dizziness.

 • 2.2 Label elements
 • Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



- · Signal word Danger
- *Hazard-determining components of labelling:* ethyl acetate butanone methyl acetate

(Contd. on page 2)

GB

Version number 1

Revision: 17.04.2018

#### Trade name: Reparatur-Set für Pool-Folien

acetone	(Contd. from page 1)
· Hazard stateme	nte
	nmable liquid and vapour.
	rious eye irritation.
	drowsiness or dizziness.
Precautionary s	
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves / eye protection.
P305+P351+P33	38 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national/
	international regulations.
· Additional infor	
EUH066 Repeat	ed exposure may cause skin dryness or cracking.
· 2.3 Other hazar	
	and vPvB assessment
DBT. Not opplied	

- **PBT:** Not applicable.
- vPvB: Not applicable.

# SECTION 3: Composition/information on ingredients

#### · 3.2 Chemical characterisation: Mixtures

· Description: Mixture of the substances listed below including additives not requiring identification.

<ul> <li>Dangerous components:</li> </ul>		
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-X	ethyl acetate Flam. Liq. 2, H225; (1) Eye Irrit. 2, H319; STOT SE 3, H336	25 - 50%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-X	butanone Flam. Liq. 2, H225; (1) Eye Irrit. 2, H319; STOT SE 3, H336	10 - 25%
CAS: 79-20-9 EINECS: 201-185-2 Reg.nr.: 01-2119459211-47-X	methyl acetate Flam. Liq. 2, H225; (1) Eye Irrit. 2, H319; STOT SE 3, H336	10 - 25%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-X	acetone Flam. Liq. 2, H225; (1) Eye Irrit. 2, H319; STOT SE 3, H336	10 - 25%
<ul> <li>Additional information For th</li> </ul>	e wording of the listed hazard phrases refer to section 16	

Additional information For the wording of the listed hazard phrases refer to section 16.

# **SECTION 4: First aid measures**

#### · 4.1 Description of first aid measures

· General information Remove contaminated clothing immediately.

· After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness bring patient into stable side position for transport.

#### · After skin contact

Wash intensively with water and soap. Use protective skin ointment.

If skin irritation continues, consult a doctor.

(Contd. on page 3)

GB

Version number 1

Revision: 17.04.2018

#### Trade name: Reparatur-Set für Pool-Folien

· After eye contact

Keep eye lids open and rinse them with ample amounts of clean running water for at least 15 minutes.

Seek medical treatment.

- After swallowing Avoid vomiting. Don't give anything to drink. Immediately consult physician.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

# **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents
- CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- · For safety reasons unsuitable extinguishing agents Water with a full water jet.
- 5.2 Special hazards arising from the substance or mixture
- Can form explosive gas-air mixtures. Carbon monoxide and carbon dioxide
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained breathing apparatus.

# **SECTION 6: Accidental release measures**

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Keep away from sources of ignition and care for sufficient ventilation due to the content of organic solvents.

Do not inhale vapours.

6.2 Environmental precautions:

Prevent material from reaching sewage system, holes and cellars. Inform respective authorities in case product reaches water or sewage system. Do not allow to enter drainage system, surface or ground water.

- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders). Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- 6.4 Reference to other sections See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

# SECTION 7: Handling and storage

7.1 Precautions for safe handling
 Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
 Prevent formation of aerosols.
 Avoid splashes or spray in enclosed areas.

 Information about protection against explosions and fires:
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Use explosion-proof apparatus / fittings and spark-proof tools.
 Vapours are heavier than air and may travel long distances along ground, ignite and flash back to source.

(Contd. on page 4)

(Contd. from page 2)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.04.2018

Version number 1

Revision: 17.04.2018

#### Trade name: Reparatur-Set für Pool-Folien

(Contd. from page 3)

- 7.2 Conditions for safe storage, including any incompatibilities
   Storage
- *Requirements to be met by storerooms and containers:* Store cool and dry in well sealed containers. Ensure sufficient ventilation.
- Information about storage in one common storage facility: Keep away from food, drink and animal feeding stuffs.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

#### • Components with limit values that require monitoring at the workplace: WEL: workplace exposure limit

IOELV: Indicative Occupational Exposure Limit Values, workplace threshold value of the European Union

#### 141-78-6 ethyl acetate WEL (Great Britain) Short-term value: 400 ppm Long-term value: 200 ppm Short-term value: 1468 mg/m<sup>3</sup>, 400 ppm **IOELV** (European Union) Long-term value: 734 mg/m<sup>3</sup>, 200 ppm 78-93-3 butanone WEL (Great Britain) Short-term value: 899 mg/m<sup>3</sup>, 300 ppm Long-term value: 600 mg/m<sup>3</sup>, 200 ppm Sk, BMGV **IOELV** (European Union) Short-term value: 900 mg/m<sup>3</sup>, 300 ppm Long-term value: 600 mg/m<sup>3</sup>, 200 ppm 79-20-9 methyl acetate WEL (Great Britain) Short-term value: 770 mg/m<sup>3</sup>, 250 ppm Long-term value: 616 mg/m<sup>3</sup>, 200 ppm 67-64-1 acetone Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm WEL (Great Britain) Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm IOELV (European Union) Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm · Ingredients with biological limit values: 78-93-3 butanone BMGV (Great Britain) 70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one · Additional information: The lists that were valid during the compilation were used as basis. · 8.2 Exposure controls · Personal protective equipment · General protective and hygienic measures Keep away from foodstuffs, beverages and food. Take off all contaminated clothing immediately. Wash hands during breaks and at the end of the work. Use skin protection cream for preventive skin protection. Do not eat, drink or smoke while working.

Avoid contact with the eyes and skin.

(Contd. on page 5)

<sup>-</sup> GB

Version number 1

Revision: 17.04.2018

#### Trade name: Reparatur-Set für Pool-Folien

(Contd. from page 4)

· Breathing equipment: In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air. · Protection of hands: · Material of gloves Butyl rubber, BR · Penetration time of glove material In case of a layer thickness of 0.7 mm the penetration time is longer than 120 minutes. Value for the permeation: Level = 4 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. • As protection from splashes gloves made of the following materials are suitable: Natural rubber, NR • Eye protection: Tightly sealed safety glasses. SECTION 9: Physical and chemical properties · 9.1 Information on basic physical and chemical properties · General Information · Appearance: Form: Liquid Colour: Different according to colour

Odour:	Solvent-like	
Change in condition		
Melting point/freezing point:	-73 °C	
Initial boiling point and boiling ra	<i>nge:</i> 70 ℃	
Flash point:	-10 °C	
Ignition temperature:	408 ℃	
Explosive properties:	Product is not explosive. However, formation of explosive air/steam mixtures is possible.	
Critical values for explosion:		
Lower:	1.2 Vol %	
Upper:	7.5 Vol %	
Vapour pressure:	Not determined.	
Density	Not determined	
Relative density	Not determined.	
Solubility in / Miscibility with		
Water:	Insoluble	
Viscosity:		
dynamic:	Not determined.	
kinematic:	Not determined.	
Solvent content:		
Organic solvents:		
VOC EU	510 g/L	
<i>9.2 Other information</i> No further relevant information available.		

(Contd. on page 6)

GE

Version number 1

Revision: 17.04.2018

#### Trade name: Reparatur-Set für Pool-Folien

(Contd. from page 5)

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

None in case of intended use and storage in compliance with instructions.

# SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- Skin corrosion/irritation Longer or repeated contact with the product reduces the natural readipogenesis of the skin and results in the desiccation of the skin. That product can be absorbed via the skin.
- · Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

# **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

(Contd. on page 7)

GB

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.04.2018

Version number 1

Revision: 17.04.2018

# Trade name: Reparatur-Set für Pool-Folien

(Contd. from page 6)

# SECTION 13: Disposal considerations

#### · 13.1 Waste treatment methods

#### · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

The waste code numbers mentioned are recommendations based on the probable use of the product.

· European	n waste catalogue
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 04 00	wastes from MFSU of adhesives and sealants (including waterproofing products)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
HP 3	Flammable
HP 4	Irritant - skin irritation and eye damage
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

#### · Uncleaned packagings:

#### · Recommendation:

Dispose of packaging according to regulations on the disposal of packagings. Packaging can be reused or recycled after cleaning.

Cleaned packing materials have to be admitted to local recycling circuits.

14.1 UN-Number ADR, IMDG, IATA	UN1133
14.2 UN proper shipping name ADR IMDG, IATA	1133 ADHESIVES, special provision 640C ADHESIVES
14.3 Transport hazard class(es)	
ADR	
Class Label	3 (F1) Flammable liquids. 3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	

Version number 1

Revision: 17.04.2018

#### Trade name: Reparatur-Set für Pool-Folien

	(Contd. from page
<ul> <li>14.5 Environmental hazards:</li> <li>Marine pollutant:</li> </ul>	No
<ul> <li>14.6 Special precautions for user</li> <li>Kemler Number:</li> <li>EMS Number:</li> </ul>	Warning: Flammable liquids. 33 F-E,S-D
· Stowage Category	В
<ul> <li>14.7 Transport in bulk according to An of Marpol and the IBC Code</li> </ul>	Not applicable.
· Transport/Additional information:	
<ul> <li>ADR</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> <li>Transport category</li> </ul>	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml 2
• Tunnel restriction code	D/E
<ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1133 ADHESIVES, SPECIAL PROVISION 640C, 3, II

# **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- · National regulations
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Substances of very high concern (SVHC) according to REACH, Article 57
- None of the ingredients is contained.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

(Contd. on page 9)

GB

Version number 1

Revision: 17.04.2018

# Trade name: Reparatur-Set für Pool-Folien

	(Contd. from page
· Department issuing data specification sheet:	
This Material Safety Data Sheet has been drawn up in coopera	ation with:
DEKRA Assurance Services GmbH, Hanomagstr. 12, D-30449	
phone: (+49) 511 42079 - 0, reach@dekra.com.	,
© DEKRA Assurance Services GmbH. Changing this documer	nte is subject to explicit acceptance
by DEKRA Assurance Services GmbH.	
· Abbreviations and acronyms:	
ADR: Accord européen sur le transport des marchandises dangereuses par F	Route (European Agreement concerning the
International Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemica	ale
EINECS: European Inventory of Existing Commercial Chemical Substances	ais
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society	/)
PBT: Persistent, Bioaccumulative and Toxic	,
SVHC: Substances of Very High Concern	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 2: Flammable liquids – Category 2	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	