

Technical data sheet



Non-drip grease for cold and hot water fittings.

Supple, smooth non-drip grease for fittings, machines and equipment, applicable in food production for unpredictable product contact.

Advantages and Properties:

food-safe
non-drip
smooth
EP high pressure lubricant
good water resistance, good corrosion protection
reliable
Temperature range: -20°C to +140°C(short-term 180°C)
NLGI class: 2

Areas of application:

Suitable for lubricating tasks under high pressure at medium and slow speeds. Also suitable for machines and equipment where Glissa fitting grease comes into occasional contact with food or drinking water.

Use e.g. for the lubrication of roller and sliding bearings in packaging and filling plants for foodstuffs, for the lubrication of screw conveyors in the sugar industry or on conveyor belts, for the lubrication of fittings or tap plugs in the sanitary sector, etc.

Tests and approvals:

According to NSF -H 1 food quality.

Application:

Clean surfaces from old grease or residues. Use suitable aids for application and even distribution.

Shelf life and storage:

Can be stored for 3 years at a temperature between 5°C and 40°C. The expiry date applies to an unopened product stored at 20°C and normal humidity.

Article number, packaging & packaging units:

Article no.	Article	PU
15003	14 g tube	60
15002	30 g tube	40
15001	60 g tube	20

Note :

All information and recommendations contained in this technical data sheet do not constitute guaranteed properties. They are based on our research results and experience. However, they are not binding. A guarantee can only be given for the consistently high quality of our products. We recommend that you carry out your own tests.

The user bears the sole responsibility for incorrect use of the product.

Safety and health:

See safety data sheet

