

Technical data sheet



Non-drip lubricating grease for drinking water valves and fittings

Glissa silicone grease is water-repellent, physiologically safe, sealing and has a high temperature resistance up to 200°C.

Advantages & Features

- Suitable for drinking water (hot and cold)
- Non dripping
- O-ring compatible (NBR, EPDM)
- Resistant against many chemicals
- water repellent; sealing
- Neutral, odourless and tasteless
- Temperature range: -40°C to +200°C
- Physiologically harmless

Application areas

Glissa silicone grease is suitable as a lubricant and sealant for drinking water fittings (e.g. cartridges for single-lever mixers, switching valves and swivel spouts),

Tests and Approvals

Corresponds to the guidelines of the KTW-BWGL, WRAS, NSF H-1, eurofins and approved according to DIN EN ISO 21469.

Application

Clean surfaces of old grease or residue. Apply the fittings grease with suitable tools and spread evenly to cover it.

Shelf life and storage

3 years when stored in a dry and dark place at normal humidity and room temperature.

Order number, article and packing unit

Order-no.	Article	PU
15007	3 g bag	On demand
15014	7 g tube	80
15015	23 g tube	40
15021	60 g tube	20

Notice

All information and recommendations contained in this technical data sheet do not represent guaranteed properties. They are based on our research results and experience. However, they are non-binding as we are not responsible for compliance with the processing conditions may be, since we do not know the special application conditions at the user.

A guarantee can only be given for the consistently high quality of our products. We recommend that you conduct sufficient tests to determine whether the specified product has the properties you want. A claim from this is excluded. The processor bears sole responsibility for incorrect or inappropriate use.

Safety and health

See safety data sheet



3 g bag Glissa Silicone Grease