

## Technical data sheet



### High-grade lubricant for gas valves and fittings and actuators in accordance with DIN EN 377.

Glissa all gas valve grease is resistant to all gases and gas mixtures mentioned in DVGW worksheet G 260. It is also used Temperature range: to +150 °C packings or elastomer seals etc.

#### Vorteile u. Eigenschaften

- Synthetic
- Non dripping
- Smooth
- Suitable for gas valves and fittings
- Temperature range: -20°C to +150 °C

#### Application areas

Also used to lubricate cock plugs or sealing elements such as membranes, packing or elastomer seals, etc.

#### Tests and Approvals

Corresponds to DIN DVGW 96.01e1055.

#### Application

Clean surfaces of old grease or residue. Use suitable tools for application and even distribution.

#### Shelf life and storage

3 years shelf life when stored in a dry and dark place at normal humidity and room temperature.

#### Order number, article and packing unit

Order-no.	Article	PU
15010	20 g Tube	12

#### Notice

All information and recommendations contained in this technical data sheet do not represent guaranteed properties. They are based on our research results and experience. However, they are non-binding as we are not responsible for compliance with the processing conditions may be, since we do not know the special application conditions at the user.

A guarantee can only be given for the consistently high quality of our products. We recommend that you conduct sufficient tests to determine whether the specified product has the properties you want. A claim from this is excluded. The processor bears sole responsibility for incorrect or inappropriate use.

#### Safety and health

See safety data sheet