

Technical data sheet



For the cleaning of connections made of PVC and ABS before gluing

Advantages & Features

- Easy to use
- Works immediately
- Reliable and safe
- Density: 0.8 g/ml
- Viscosity: 1mPa`s

Application areas

Fermitac PVC + ABS Cleaner is a cleaning agent for pipes, sleeves and fittings made of PVC + ABS.

Tests and Approvals

./.

Use

Moisten clean, absorbent paper with FERMITAC PVC+ABS cleaner and clean the surfaces to be bonded. Before you apply the adhesive, allow the cleaned parts to dry first. Immediately remove condensation water caused by rapid cooling of the cleaner with absorbent paper. FERMITAC PVC+ABS cleaner is not suitable for diluting adhesives!

Shelf life and storage

24 months in the original sealed container
Storage temperature between 5°C to 35°C

Order number, article and packaging units

Order-no.	Article	PU
22001	125 ml bottle	12
22003	1 l bottle	6

Notice

All information and recommendations contained in this technical data sheet do not represent guaranteed properties. They are based on our research results and experience. However, they are non-binding as we are not responsible for compliance with the processing conditions may be, since we do not know the special application conditions at the user.

A guarantee can only be given for the consistently high quality of our products. We recommend that you conduct sufficient tests to determine whether the specified product has the properties you want. A claim from this is excluded. The processor bears sole responsibility for incorrect or inappropriate use.

Safety and health:

See safety data sheet