

Fleece Glue PRO

Functionality

Synthetic resin-based aqueous glue, supplied in buckets, for gluing swimming pool felts between the base (wood, concrete, polystyrene, etc.) and the liner.

- Easy to use thanks to its texture that does not run when applied vertically, and its good adhesive properties
- Compatible with all felts and materials normally used in swimming pool bases
- Antifungal treatment to protect it from microorganisms (e.g.: mildew)



Technical Characteristics

Spezifikationen	Characteristics
Appearance	Thixotropic non-running paste
Nature	Synthetic resin-based aqueous glue
Colour	White, transparent after drying
Density	1,08
Open time	15 min.
Final drying time	72 h.
Application temperature	+10°C up to +30°C
Temperature resistance of the glue when dry	-10°C up to +70°C
Adhesion	Good on all the usual swimming pool bases such as concrete, wood, polystyrene, polyester, etc. Compatible with all felts on the market, made from PE, PP or polyester.
Resistance	Good resistance to treated swimming pool water

Technical data sheet



Erstellt am: 03/01/2020

Version: 1

Use

Preparation

- The surfaces to be bonded must be clean and dry.
- The temperature must be in the range of +10°C to +30°C.

Application

- Apply the glue to the base, with a roller or spatula. Coating may be over the whole surface to avoid pleats, or in strips / spots on part of the surface. It is preferable to coat at least the surrounding area, the corners and outside edge of the parts to be sealed and to deposit the glue at regular intervals
- Install the felt within 15 minutes, pressing it hard against the base.
- Final drying after 72 hours.

Consumption

A 5 kg bucket suffices to glue an area of 50m² if the whole of the area is covered.

Material Cleaning

Fresh glue can be removed with water. Once dry, the glue can only be removed mechanically, or with a solvent such as acetone.

Storage

Store at a temperature between +5°C and +30°C (protect from freezing). The expiry date on the packaging is for unopened product; store at 20°C in normal hygrometry conditions.

Comments

If you are looking for a faster initial glue you can use pool fermit Spray glue for Pool Fleece or pool fermit Spray glue Poly for sensitive surfaces(Polystyrene)

Safety Precautions

The Material Safety Data Sheet is available on the Internet on www.fermit.com

The information contained on the technical datasheet is provided in all good faith and results from measurements made in our laboratory. Given the number of materials, differences in quality and diversity of working methods, we recommend that users perform tests prior to application under actual conditions of use. This document may be amended in keeping with product development and the state of our knowledge without prior notice and therefore it is recommended to check that you have the latest version before use. The safety data sheet is available online at www.fermit.com